Application No.: 10/585,109

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the

application:

LISTING OF CLAIMS:

1. (currently amended): A hydrocarbon-producing-catalyst obtainable for the

Fischer-Tropsch reaction, which produces hydrocarbons from syngas and is obtained by

supporting a ruthenium compound on a support composed of a manganese oxide and an

aluminum oxide, and which satisfies at least one of characteristics (1) and (2):

(1) the catalyst being treated with an aqueous alkaline solution and subsequently

subjected to calcination treatment in the air at 150 to 500°C,

(2) the aluminum oxide being an aluminum oxide in which pore volume formed by

pores having a pore diameter of 8 nm or more accounts for 50% or more of total pore volume.

wherein at least one sodium compound is further supported on the support.

2. (original): The catalyst according to claim 1, wherein the supported amount of

the ruthenium compound is from 0.5 to 5% by weight in terms of ruthenium metal on the basis of

the catalyst before the treatment with the aqueous alkaline solution and the calcination treatment.

3. (canceled).

4. (currently amended): The catalyst according to claim 31, wherein the supported

amount of at least one-compound selected from alkali-metal-the sodium compounds, alkaline

earth metal compounds, and rare earth metal compounds_is from 0.01 to 3% by weight in terms

7

Application No.: 10/585,109

of oxide on the basis of the catalyst before the treatment with the aqueous alkaline solution and the calcination treatment.

Claims 5-6. (canceled).

7. (withdrawn): A process for producing hydrocarbons, which comprises bringing a mixed gas containing hydrogen and carbon monoxide into contact with the catalyst according to any one of claims 1 to 6.

- 8. (withdrawn): A process for producing a hydrocarbon-producing catalyst, which comprises treating, with an aqueous alkaline solution, a catalyst obtainable by supporting a ruthenium compound on a support composed of a manganese oxide and an aluminum oxide and subsequently subjecting the catalyst to calcination treatment in the air at 150 to 500°C.
- 9. (withdrawn): The process according to claim 8, wherein the supported amount of the ruthenium compound is from 0.5 to 5% by weight in terms of metal on the basis of the catalyst before the treatment with the aqueous alkaline solution and the calcination treatment.
- 10. (withdrawn): The process according to claim 8 or 9, wherein at least one compound selected from alkali metal compounds, alkaline earth metal compounds, and rare earth metal compounds is further supported on the support.
- 11. (withdrawn): The process according to claim 10, wherein the supported amount of at least one compound selected from alkali metal compounds, alkaline earth metal

Application No.: 10/585,109

calcination treatment.

compounds, and rare earth metal compounds is from 0.01 to 3% by weight in terms of oxide on the basis of the catalyst before the treatment with the aqueous alkaline solution and the

12. (withdrawn): The process according to any one of claims 8 to 11, wherein the ratio of the manganese compound is from 10 to 70% by weight on the basis of the catalyst before

the treatment with the aqueous alkaline solution and the calcination treatment.

13. (withdrawn): The process for producing the catalyst

according to any one of claims 10 to 12, wherein at least one compound selected from alkali metal compounds, alkaline earth metal compounds, and rare earth metal compounds is a sodium compound.

14. (withdrawn): A process for producing hydrocarbons, which comprises bringing a mixed gas containing hydrogen and carbon monoxide into contact with the catalyst obtained by the production process according to any one of claims 8 to 13.

- 15. (canceled).
- 16. (canceled).

17. (currently amended): The catalyst according to any one of claims 1, 2, 3, 4, 15 or 161, 2 or 4, wherein the ratio of the manganese compound is from 10 to 70% by weight on the basis of the catalyst before the treatment with the aqueous alkaline solution and the calcination treatment.

9

Application No.: 10/585,109

Claims 18-20. (canceled).

21. (new): A process for producing hydrocarbons by the Fischer-Tropsch reaction, which process comprises contacting syngas under Fischer-Tropsch reaction condition with the catalyst of claim 1 for a time sufficient to produce said hydrocarbons.

22. (new): The process of claim 21, wherein the syngas contains hydrogen and carbon monoxide as main components at a partial pressure ratio of hydrogen/carbon monoxide of 0.6 to 2.7, and the reaction is conducted at 200 to 350°C.